

FLACA

LED TRIAC

driver/alimentatore: OPTOTRONIC® - OTe35/220-240/700 PC

LIST OF PHASE CUT DIMMERS TESTED FOR COMPATIBILITY LISTA DIMMER COMPATIBILI PER DIMMERAZIONE A TAGLIO DI FASE

| Brand | Model Number | L/T | OTe35/220-240/700 PC | |
|--------------|------------------|-----|----------------------|---------|
| | | | dim min | dim max |
| Busch | 2247U | L | NA | |
| Busch | 6523U | L | 3% | 100% |
| Busch | 6513U-102 | T | 24% | 100% |
| Busch | 2250 | L | 6% | 100% |
| Clipsal | 32E450 TM | T | NA | |
| Clipsal | 32E450UM | T | 17% | 100% |
| Clipsal | 32E2CFLDM | L | 12% | 100% |
| Clipsal* | 32E450LM | L | 6% | 100% |
| ELKO* | 315 GLE | T | 7% | 100% |
| ELKO* | 400 GLI | L | 4% | 100% |
| Feller* | 40600.RL | L | 3% | 100% |
| GIRA | 0307 00/I01 | T | 4% | 100% |
| Hager B&R | WBMD400TO | T | 30% | 100% |
| HPM | cat 400T | T | 3% | 100% |
| HPM | Cat 200L | L | 9% | 100% |
| Jung | 225TDE | T | 4% | 100% |
| Jung* | 225NVDE | L | 4% | 100% |
| Legrand | Cat 400L | T | 3% | 100% |
| Legrand | Cat 400T | L | 3% | 100% |
| Legrand | ZLD03 | T | 20% | 100% |
| Legrand | 078407 | L | 5% | 100% |
| Legrand | 067083 | T | 1% | 100% |
| Legrand | 770062 | T | 0% | 100% |
| TCL-Legrand | 775903 | T | 3% | 100% |
| Lutron* | GRX-3106-T-AU-WH | L | 0% | 100% |
| Lutron (USA) | GXI-3104-T-CE-WH | T | 0% | 100% |
| NIKO | 310-01900 | T | 2% | 100% |
| NIKO | 330-00700 | T | 0% | 100% |
| NIKO | 310-02700 | T | 13% | 100% |
| NIKO | 310-02800 | T | 2% | 100% |
| OSRAM | HTi DALI 315 DIM | T | 14% | 100% |
| OSRAM | MCU Te250 | T | 9% | 100% |
| Siemens | 5TC8 284 | T | 5% | 100% |

* Functionality at the minimum load to be checked

Compatibility proven in respect of linear dimming behaviour in the range given by the dimmer and absence of flashing and flickering.
Max. dimming level depending on the construction of the dimmer